



This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

Indirizzo	Sicherheitsglastechnik Oelsnitz (Vogtl.) GmbH
	Talstraße 2
	D-08606 Oelsnitz (Vogtl.)

Nazione

Germania

PRODOTTI O MACCHINARI

Toughened Glass

Toughened safety glass is made via a thermal toughening process. A heating and cooling process distribute the stress in the glass. The glass is heated to a temperature above 620°C, and then air-cooled. This sudden cooling induces tensile stresses in the centre of the glass balanced by compressive stresses in the surface.

If broken, this equilibrium of stresses is destroyed and the glass crumbles into small pieces that have blunt edges. The benefits of toughened safety glass are its increased bending, impact, shock and thermal shock resistance.

As a result of its safety toughened safety glass can be used for exterior and interior applications.

Product Range / Production Options Toughened Glass

Maximum size 9,000mm x 3,300mm Thickness range between 4mm - 19mm Edge working Mitered edges Drilled holes Countersunk holes Corner cut-outs Edge cut-outs Centre cut-outs Round corners Shaped glass Fully enamelled glass, screen printing

Heat Strengthened Glass

Heat strengthened glass undergoes a similar manufacturing process as toughened glass. The only difference is the significantly slower cooling process. By cooling the glass at a slower pace less stress is induced in the glass. This results in heat strengthened glass having a similar breakage pattern as float glass. Heat strengthened glass can only be regarded as safety glass when used in laminated glass.

Product Range / Production Options Heat Strengthened Glass

Maximum size 9,000mm x 3,300mm Thickness range between 4mm - 12mm Edge working Mitered edges Drilled holes Countersunk holes Corner cut-outs Edge cut-outs Centre cut-outs Round corners Shaped glass Fully enamelled glass, screen printing

Laminated Safety Glass

Laminated safety glass consists of at least two panes of either float glass, toughened glass or heat strengthened glass firmly bonded with viscoelastic, highly tear resistant Polyvinyl Butyrall (PVB) interlayers.





In the event of breakage, the glass fragments are retained by the interlayer. The thickness of the interlayer affects the remaining load capacity. The benefits of laminated safety glass are its bending and impact resistance and its ability to resist high temperatures. Depending on the panes, SGT's laminated safety glass has the following benefits:

protection from glass fallout in overhead glazing impact resistance intrusion resistance blast resistance

Product Range / Production Options Laminated Safety Glass

Maximum size 9,000mm x 3,300mm Thickness range between 4mm - 19mm Edge working Mitered edges Drilled holes Countersunk holes Corner cut-outs Edge cut-outs Centre cut-outs Round corners Shaped glass Fully enamelled glass, screen printing

Enamelling

SGT uses enamels to provide toughened glass in a range of different colours. Enamels can be applied onto any smooth-surfaced flat glass that can be toughened. The enamels are rolled onto the surface and then fired onto the glass at temperatures between 600 and 620°C. Please note that due to applying the enamels by rolling, the entire glass sheet will be enamelled.

Screen printing

Company Profile of Sicherheitsglastechnik Oelsnitz (Vogtl.) GmbH

A service of glassglobal.com, an affiliate of glassglobal group.

Il materiale informativo del sito è registrato ed appartiene all'azienda o ai terzi che lo hanno fornito e tutti i diritti sono riservati. Qualsiasi utente che accede a tale materiale può farlo solo ad uso personale e ne è anche responsabile. Ridistribuzione o altro uso commerciale di tale materiale è espressamente proibito. Nel caso in cui il materiale sia stato ceduto da terzi, l'utente concorda di rispettare questi termini di utilizzo specificati. Glass Global non garantisce la veridicità o l'esattezza del contenuto di alcuna informazione o di siti web esterni menzionati nelle stesse.www.glassglobal.com - The International Portal to the Glass Industry - OGIS GmbH